APC NetShelter Rack PDU Advanced, Metered, 7.4kW, 1Phase, 230V, 32A, 332P6, 40 Outlets

APDU10150ME

Overview

Lead Time Usually in Stock	
----------------------------	--

Main

Colour	Black
Product Or Component Type	PDU
Pdu Type	Metered
Cable Length	3.0 m

Complementary

Main Input Voltage	230 V 1 phase
Height	149.0 cm
Width	5.6 cm
Main Output Voltage	230 V
Depth	7.5 cm
Net Weight	6.2 kg
Mounting Location	Side
Mounting Preference	No preference
Input Connection Type	IEC 60309 32 A 2P + PE
Mounting Mode	Rack-mounted
Number Of Rack Unit	0U
Mounting Position	Vertical
Communication Port Protocol	1000BASE-T 10/100BASE-T
[In] Rated Current	32 A
Permissible Voltage	200240 V
Input Current Limits	32 A
Load Capacity	7400 VA
Network Frequency	50/60 Hz
Number Of Power Socket Outlets	20 C13/C15/C19/C21 20C13/C15

Environment

Product Certifications	TAA compliance UKCA
Standards	CE EN 62368-1
Ambient Air Temperature For Operation	-560 °C
Relative Humidity	595 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	595 %
Storage Altitude	0.0015240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	172 cm
Package 1 Width	11.6 cm
Package 1 Length	20.8 cm
Package 1 Weight	8.2 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >

Well-being performance

