



APC Smart-UPS On-Line, 1000VA, Lithium-ion, Rackmount 4U, 230V, 8x C13 IEC outlets, SmartSlot, Extended long runtime, Rail kit included

SRTL1000RM4UXLI

Overview

Presentation	High density, double-conversion on-line power protection with long runtime.
Lead Time	Usually in Stock

Main

wain	
Main Input Voltage	230 V
Other Input Voltage	220 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Rated Power In W	900 W
Rated Power In Va	1000 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	8 IEC 60320 C13
Number Of Rack Unit	4U
Cable Length	1.83 m
Number Of Cables	1

Batteries & Runtime

Run Time	View Runtime Graph ☐
Battery Type	Li-lon (Lithium-lon)
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Voltage	48 V
Battery Charger Power	103 W rated
Battery Life	510 year(s)
Extended Runtime	1

General

Ups Type	Double conversion online
Product Web Sub-Family	Lithium-lon
Number Of Power Module Free Slots	0
Number Of Power Module Filled	0

Redundant No

Physical

•	
Colour	Black with silver front bezel
Height	8.5 cm
Width	43.2 cm
Depth	56 cm
Net Weight	13.7 kg
Mounting Preference	No preference
Mounting Mode	Rack-mounted with kit
Two Post Mountable	0
Usb Compatible	Yes
Mounting Position	Horizontal Vertical

Input

Network Frequency	4070 Hz auto-sensing
Input Voltage Limits	160275 V

Output

Maximum Configurable Power In Va	1000 VA
Maximum Configurable Power In W	900 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains
Wave Type	Sine wave
Harmonic Distortion	Less than 2 %
Crest Factor	3:1
Bypass Type	Built-in bypass

Conformance

Product Certifications	CE	
Marking	CE Mark	

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 % non-condensing
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-1545 °C
Storage Relative Humidity	095 % non-condensing
Storage Altitude	0.0015240.00 m
Acoustic Level	50 dBA
Heat Dissipation	400 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Free Slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off	Yes

Surge Protection and Filtering

Surge Energy Rate 340 J

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	60 cm
Package 1 Length	81 cm
Package 1 Weight	21 kg

Contractual warranty

12 Feb 2024

Warranty 5 year repair or replace

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information