Ubiqiuti G5 Dome Ultra

Technical Specifications

Mechanical

Dimensions Ø63.6 x 68.2 mm (Ø2.5 x 2.7")

Weight 175 g (6.2 oz)

Enclosure material Aluminum alloy, polycarbonate

Mount material Stainless steel

Resistance IK06

Optics

Sensor 1/2.4" CMOS

Lens Fixed focal length

View angle H: 102.4°, V: 54.9°, D: 120.6°

Night mode Built-in IR LED illumination and IR cut filter

IR distance 20 m (65 ft)

Video

Resolution 4MP 2688 x 1512 (16:9)

Max. frame rate 30 FPS

Image settings Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

System

Processor Dual-core Arm® Cortex®-A7 based chip

Networking interface 10/100 MbE RJ45 port

Max. power consumption 4.2W

Power method PoE

Supported voltage range 37–57V DC

Button Factory reset

Mounting Surface mount

Ambient operating temperature -20 to 40° C (-4 to 104° F)

Ambient operating humidity 10 to 90% noncondensing

Certifications FCC, IC, CE

Software

Web application UniFi Protect

Mobile app UniFi Protect iOS™ and Android™